

Stand-Alone Speech System

Model 238350

SPECIFICATIONS

- Size: 3" X 4"
- Processor: TMS50C20
- Power: 5Vdc @ 75 mA
- Vocabulary: 256 Words, MAX
- PROM Capacity: 27C256, 27C512
- Controls: Word Address, Speak, Volume
- Interface: 8 Bit Parallel, with Strobe and Ready
- Connectors: .025" X .1" Headers
- Speaker Impedance: 8 OHMS
- Output Power: 300 MW



APPLICATIONS

The model 238350 Speech Board provides random access to a maximum of 256 pre-recorded words or phrases. The LPC algorithms best suited for limited memory applications where words and phrases must be concatenated to form sentences on a real-time basis. It can be used in telephone interfaces, audio annunciation, alarm annunciators and training systems. The speech for this product must be encoded by ATL, Texas Instruments or the customer using specialized equipment.

CONSTRUCTION

The Speech Board is constructed on a single printed circuit board. Switches are provided on the board for word selection and speech initiation. These functions,

along with speaker and power connections, are also brought out to single row headers for convenient interfacing to other equipment. A standard parallel interface is provided to control the product from an IBM compatible external computer.

CUSTOMIZATION

ATL can provide customization of its products, or the development of new products to meet specific customer requirements. Enclosures, custom interfaces and vocabulary development are but a few examples of what can be requested. ATL is prepared to provide these services in a cost-effective manner and in a timely fashion.



ATL applies tomorrow's technology today

ADVANCED TECHNOLOGY LABORATORIES